

PT.25

Polyester Film /Non-woven Electrical Tape

General Description:

90 micron Polyester film/Non-woven laminate coated on one side with thermosetting rubber adhesive. Designed for insulating, holding and banding in transformers and motors.

Product Features And Applications:

- Excellent electrical properties and thermal resistance
- Puncture resistance
- Excellent solvents and chemical resistance when thermoset
- Ground and barrier insulation of electrical motors, generators, etc.
- Outer wrapping, tabbing, harnessing and anchoring leads for electrical transformers, coils, etc.



Technical data sheet

PRODUCT TYPE	Single coated
BACKING TYPE	PET film/ Non woven
ADHESIVE TYPE	Thermosetting Rubber
COLOR	White
BACKING THICKNESS	90 µm
TOTAL THICKNESS	150 µm
PEEL ADHESION AT 180° ON STEEL	5.00 N/cm
ROLLING BALL TACK	< 5 cm
TENSILE STRENGTH	30.00 N/cm
ELONGATION AT BREAK	45 %
BREAKDOWN VOLTAGE	4.80 kV
THERMAL CLASS	130 (B)
SHORT TIME TEMPERATURE RESISTANCE	160 °C
ELECTROLYTIC CORROSION	1
APPROVALS	UL file No. E178430
SHELF LIFE	12 months
STANDARD LENGTH	50 m
STANDARD WIDTH	1280 mm

International Harmonized Test Methods: ASTM D-1000, PSTC, EN 60454-2

All statements and information listed above regarding this product are typical values for general guidance, these data have not to be intended as conformity specification. These suggestions are based on tests we believe reliable, but are not guaranteed for accuracy and completeness. The user must test, evaluate and validate this product before the use, assuming risks and liability of such use. This document may be revised without prior notice, the user who downloaded it will automatically be informed of any future revisions. Suggested storage temperature is between 10°C and 30°C with 50% relative humidity.