h-old
A Saint-Gobain brand

THE SPECIALIST OF HIGH VALUE ADHESIVE TAPES

P.34 (ALL COLORS)

Polyester Film Tape

General Description:

23 micron polyester film coated with high quality acrylic adhesive. Designed for coil wrapping, inter-layer insulation, anchoring, holding, harnessing, splicing, etc.
Excellent flagging and solvent resistance.



Product Features And Applications:

- Good adhesion and initial tack
- High conformability and chemical resistance
- Motor & transformer manufacturers
- Capacitor manufacturers
- Splicing of papers & films
- Identification

Technical data sheet

PRODUCT TYPE	**Single coated**
BACKING TYPE	**PET film**
ADHESIVE TYPE	**Pure acrylic**
COLOR	**Yellow, Red, Green, Blue, Black, White**
BACKING THICKNESS	**23 µm**
TOTAL THICKNESS	**60 µm**
PEEL ADHESION AT 180° ON STEEL	**2.50 N/cm**
ROLLING BALL TACK	**< 10 cm**
TENSILE STRENGTH	**40.00 N/cm**
ELONGATION AT BREAK	**80 %**
BREAKDOWN VOLTAGE	**4.50 kV**
THERMAL CLASS	**130 (B)**
SHORT TIME TEMPERATURE RESISTANCE	**180 °C**
ELECTROLITIC CORROSION	**1**
APPROVALS	**UL file No. E178430**
SHELF LIFE	**12 months**
STANDARD LENGTH	**66 m**
STANDARD WIDTH	**1280 mm**

International Harmonized Test Methods: ASTM D-1000, PSTC, EN 60454-2

All statements and information listed above regarding this product are typical values for general guidance, these data have not to be intended as conformity specification. These suggestions are based on tests we believe reliable, but are not guaranteed for accuracy and completeness. The user must test, evaluate and validate this product before the use, assuming risks and liability of such use. This document may be revised without prior notice, the user who downloaded it will automatically be informed of any future revisions. Suggested storage temperature is between 10°C and 30°C with 50% relative humidity.

Saint-Gobain Performance Plastics h-old Spa via Valsesia 96/98 - 28061 Biandrate (NO) - ITALY
Tel. +39 0321 838833 Fax +39 0321 811322 marketing-hold@saint-gobain.com **www.h-old.com**

SAINT-GOBAIN